



raspberry harvester

Oxbo 9000 Berry Harvester

Fruit Quality

Oxbo harvesters are known for picking the highest quality fruit. Features of the Oxbo 9000 that ensure high quality include:

- **A curved belt delivery system for minimal fruit drops.** The belting system allows for high fruit volume without sacrificing fruit quality.
- **NEW Knife edge cleaning system.** Positioned at the first belt transition, this system gently and effectively blows debris out of the fruit.
- **Accommodates up to three fruit inspectors for sorting.** Allows growers to get IQF fruit when conditions are right.
- **Wide 55" picking tunnel.** With today's newer, more vigorous raspberry varieties, the wide tunnel will not compress the plant as much resulting in a better product.

Harvester Quality

Designed and built in the USA to the highest manufacturing standards and to CE compliance, the Oxbo 9000 has been built to give long lasting performance. The Oxbo 9000 also gives you automatic steering and automatic leveling for ultimate fruit retention. You can also customize your Oxbo 9000 with the many available options including:



- Big Foot tires & rims (600/40 -22.5)
- Posi-traction
- Food grade oil
- Straight belt fruit delivery system
- High density catcher plates (4 ¾ inch spacing)
- 10-inch and 18-inch side deck extensions configured with either Lexan™, stainless steel, or gate siding

Reliability

The Oxbo 9000 raspberry harvester features a reliable Cummins® diesel engine. Key components of the harvester, like pumps, hydraulic motors gearboxes, catchers, buckets, and belts have been designed for a long life.

Customized for Your Conditions

Not only does the Oxbo 9000 give you reliability, but the Oxbo 9000 gives you a choice of three different picking systems:

- **Orbirotor® System:** The unique Orbirotor utilizes an orbital shaking action that is easily adjusted to meet a wide range of picking requirements. The selective and gentle shake lets you take advantage of the early season price by allowing you to get into the field earlier than you would with any other shaking system on the market. 
- **Dynarotor® System:** Dynarotor heads use a more aggressive horizontal shaking action, which typically lends itself primarily to blueberry harvesting. Weights can be added for a more aggressive pick for clean up. 
- **Sway System:** The Oxbo 9000 also offers a traditional sway system that removes fruit by swaying the plants back and forth as a group.

Specifications

Length:	18ft 3in (5.56m)	Lift:	2ft (0.61m)
Width:	10ft 9in (3.27m)	Tunnel Width:	4ft 7in (1.40m)
Min. Height:	10ft 3in (3.12m)	Inside Catchers:	2ft 1in (0.635m)
Weight:	10,000lbs (4,545kg)	Tires:	600/40-22.5
Engine:	Cummins® 63hp diesel engine		



oxbo®

270 Birch Bay Lynden Road
Lynden, WA 98264

tel 360.354.1500
fax 360.354.1300
www.oxbocorp.com